

NP-660T

5.6" QVGA TOUCH PANEL SYSTEM WITH CE 5.0



FEATURES

- 5.6" LCD Display
- Analog resistive touch screen
- NEMA 4 Front Panel
- CIRRUS LOGIC EP9135 processor
- 1 Ethernet port
- 3 Serial ports
- 2 USB ports (12Mbps) Full Speed
- Fan-less construction
- 1 Compact Flash slot
- Platform SDK

CE 5.0 (CE.NET) FEATURES

- Pocket Internet Explorer
- Real-time processing with 256 priority levels and nested interrupt support
- .NET Compact Framework 2.0
- RDP Thin Client
- XML Web Services, SOAP, and WSDL
- Application programming with Visual Studio 2005 and many other application development tools.

INTRODUCTION

The NP-660T is a miniature and compact platform that is designed for small-sized operator interface market. It has a 5.6" TFT QVGA LCD display that offers a cost effective and powerful choice. At its foundation is a CIRRUS LOGIC EP9135 200MHz processor design with a memory management unit (MMU), that supports Windows CE. The ARM920T's 32-bit microcontroller architecture, with a five-stage pipeline, delivers impressive performance at very low power.

The NP-660T has a 10 Base-T Ethernet port for responsive open communications. The NP-606S integrates Windows CE 5.0 (CE.NET) which expands its capabilities with vast embedded tools. Windows CE 5.0 features real time capabilities, IE6., RDP, and custom programming with Visual Studio 2005 and many other application development tools.

SPECIFICATIONS

- Display: 5.6" QVGA Color TFT LCD
- Resolution: 320 X 234
- Luminance: 500 cd/m²
- Contrast ratio: 150:1
- 200 MHz. CIRRUS LOGIC EP9135
- 64 MB RAM
- 32 MB ROM
- 1 Compact Flash slot for application storage
- 3 serial ports (2-RS232, 1-RS485 2W/4W)
- 2 USB ports 2.0 (12Mbps) Full Speed
- 1 Ethernet port (10/100 Base-T)
- 20 bit Stereo sound output
- Built in RTC
- NEMA4 / IP65 Front Panel
- Power input: 24 VDC, 0.5A maximum
- Dimensions: (W x H x D): 204 x 150 x 48mm (8.2" X 6" X 1.9")
- Weight: .85 kg (1.87 lbs.)
- Operating temp: 0° ~ 45°C (32° ~ 113°F)
- Relative humidity: 10% ~ 90% @ 40°C, non-condensing
- Shock (operation): 10 to 25Hz(X,Y,Z direction 2G 30minutes)
- Approvals: FCC, CE, UL (pending)